

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

PASF - Polyester approved styrene free, Comp. A

UFI: U9X0-S04H-R00D-D023

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: Chemofast Anchoring GmbH

Street: Hanns-Martin-Schleyer-Str. 23

Place: D-47877 Willich

Telephone: +49 2154 8123 0

Telefax: +49 2154 8123 333

Internet: www.chemofast.de

Responsible Department: sdb@chemofast.de

1.4. Emergency telephone number:

+49 (0)551-19240 (GIZ-Nord, German and English 24/7) Note: The product is not being placed on the market in Ireland. The SDS is used for internal purposes only.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Skin Sens. 1; H317

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Tetramethylene dimethacrylate;

Methacrylic acid, monoester with propane-1,2-diol;

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl]
(4-methylphenyl)amino]**Signal word:** Warning**Pictograms:****Hazard statements**

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 2 of 16

P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container to an approved waste disposal plant in accordance with local/national regulation.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
2082-81-7	Tetramethylene dimethacrylate			1 - < 15 %
	218-218-1		01-2119967415-30	
	Skin Sens. 1B; H317			
25013-15-4	Vinyltoluene			1 - < 8 %
	246-562-2		01-2119622074-50	
	Flam. Liq. 3, Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 2; H226 H315 H400 H411			
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			< 2,5 %
	248-666-3		01-2119490226-37	
	Eye Irrit. 2, Skin Sens. 1; H319 H317			
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]			< 0,5 %
	911-490-9		01-2119979579-10	
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H302 H315 H318 H317 H412			
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate			< 0,3 %
	229-934-9		01-2119451093-47	
	Repr. 2, Aquatic Chronic 3; H361 H412			
38668-48-3	1,1'-(p-Tolylimino)dipropen-2-ol			< 0,5 %
	254-075-1		01-2119980937-17	
	Acute Tox. 2, Eye Irrit. 2; H300 H319			
130-15-4	1,4-naphthoquinone			< 0,05 %
	204-977-6		01-2120760462-57	
	Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H330 H301 H314 H318 H317 H335 H400 H410			

Full text of H and EUH statements: see section 16.

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
2082-81-7	218-218-1	Tetramethylene dimethacrylate	1 - < 15 %
		dermal: LD50 = > 3000 mg/kg; oral: LD50 = 10066 mg/kg	
25013-15-4	246-562-2	Vinyltoluene	1 - < 8 %
		dermal: LD50 = 4585 mg/kg Aquatic Acute 1; H400: M=1	
27813-02-1	248-666-3	Methacrylic acid, monoester with propane-1,2-diol	< 2,5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 2000 mg/kg	
-	911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	< 0,5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 619 mg/kg	
6846-50-0	229-934-9	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	< 0,3 %
		dermal: LD50 = 18900 mg/kg; oral: LD50 = 3200 mg/kg	
38668-48-3	254-075-1	1,1'-(p-Tolylimino)dipropyl-2-ol	< 0,5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 25 - 200 mg/kg	
130-15-4	204-977-6	1,4-naphthoquinone	< 0,05 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: LC50 = 0,046 mg/l (dusts or mists); oral: LD50 = 124 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam
Extinguishing powder
Water spray jet

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 4 of 16

Carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For cleaning up**

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 5 of 16

Hints on joint storage

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: 5 - 25°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
25013-15-4	Methylstyrene, mixed isomers	50	242		TWA (8 h)	
		10	483		STEL (15 min)	

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 6 of 16

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
2082-81-7	Tetramethylene dimethacrylate			
Worker DNEL, long-term	inhalation	systemic	14,5 mg/m³	
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	4,3 mg/m³	
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day	
25013-15-4	Vinyltoluene			
Worker DNEL, long-term	inhalation	systemic	37 mg/m³	
Worker DNEL, acute	inhalation	systemic	37 mg/m³	
Worker DNEL, long-term	inhalation	local	37 mg/m³	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
Worker DNEL, long-term	inhalation	systemic	14,7 mg/m³	
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	8,8 mg/m³	
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day	
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]			
Worker DNEL, long-term	inhalation	systemic	9,8 mg/m³	
Worker DNEL, long-term	dermal	systemic	1,4 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	2,9 mg/m³	
Consumer DNEL, long-term	oral	systemic	0,83 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	0,83 mg/kg bw/day	
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate			
Worker DNEL, long-term	dermal	systemic	5 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	17,62 mg/m³	
Consumer DNEL, long-term	inhalation	systemic	4,35 mg/m³	
Consumer DNEL, long-term	oral	systemic	5 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	5 mg/kg bw/day	
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol			
Worker DNEL, long-term	inhalation	systemic	2 mg/m³	
Worker DNEL, long-term	dermal	systemic	0,6 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	0,3 mg/kg bw/day	
Consumer DNEL, long-term	dermal	systemic	0,3 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	0,4 mg/m³	
130-15-4	1,4-naphthoquinone			
Worker DNEL, long-term	inhalation	systemic	0,033 mg/m³	

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 7 of 16

PNEC values

CAS No	Substance	
Environmental compartment		Value
2082-81-7	Tetramethylene dimethacrylate	
Freshwater		0,043 mg/l
Marine water		0,004 mg/l
Freshwater sediment		3,12 mg/kg
Marine sediment		0,312 mg/kg
Micro-organisms in sewage treatment plants (STP)		2 mg/l
Soil		0,573 mg/kg
25013-15-4	Vinyltoluene	
Freshwater		0,05 mg/l
Marine water		0,002 mg/l
Freshwater sediment		0,684 mg/kg
Marine sediment		0,684 mg/kg
Soil		0,133 mg/kg
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	
Freshwater		0,904 mg/l
Marine water		0,904 mg/l
Freshwater sediment		6,28 mg/kg
Marine sediment		6,28 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,727 mg/kg
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]	
Freshwater		0,048 mg/l
Marine water		0,005 mg/l
Freshwater sediment		0,12 mg/kg
Marine sediment		0,12 mg/kg
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutryate	
Freshwater		0,014 mg/l
Marine water		0,001 mg/l
Freshwater sediment		5,29 mg/kg
Marine sediment		0,529 mg/kg
Soil		1,05 mg/kg
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	
Freshwater		0,017 mg/l
Marine water		0,0017 mg/l
Freshwater sediment		0,0783 mg/kg
Marine sediment		0,0072 mg/kg
Soil		0,005 mg/kg
130-15-4	1,4-naphthoquinone	
Freshwater		26,1 mg/l

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 8 of 16

Marine water	2,61 mg/l
Freshwater sediment	321 mg/kg
Marine sediment	32,1 mg/kg
Micro-organisms in sewage treatment plants (STP)	0,172 mg/l
Soil	49 mg/kg

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the paste-like component and is therefore not freely available during use. The risk of dust inhalation is excluded. Exposure limits for respirable dusts are not relevant for this product.

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear eye protection/face protection. Wear safety glasses.

Hand protection

Disposable gloves
Recommended material: NBR (Nitrile rubber)
Breakthrough time: > 480 min
Thickness of the glove material: > 0,2 mm
DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles)

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	solid (pasty)	
Colour:	light beige	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		Non-flammable.
Lower explosion limits:		not applicable

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 9 of 16

Upper explosion limits:	not applicable
Flash point:	not applicable
Auto-ignition temperature:	not applicable
Decomposition temperature:	No data available
pH-Value:	The study does not need to be conducted because the substance is known to be insoluble in water.
Viscosity / kinematic:	not applicable
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	not applicable
Vapour pressure:	No data available
Density (at 20 °C):	1,72 g/cm ³
Relative vapour density:	not applicable
Particle characteristics:	No data available

9.2. Other information**Information with regard to physical hazard classes**

Self-ignition temperature

Solid:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

No data available

Solid content:

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Response: Oxidising agent, strong

10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 10 of 16

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 50 mg/l; ATE (inhalation dust/mist) > 12,5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2082-81-7	Tetramethylene dimethacrylate				
	oral	LD50 10066 mg/kg	Rat		
	dermal	LD50 > 3000 mg/kg	Rabbit		
25013-15-4	Vinyltoluene				
	dermal	LD50 4585 mg/kg	Rabbit		
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol				
	oral	LD50 > 2000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]				
	oral	LD50 619 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutylate				
	oral	LD50 3200 mg/kg	Rat		
	dermal	LD50 18900 mg/kg	Guinea pig		
38668-48-3	1,1'-(p-Tolylimino)dipropyl-2-ol				
	oral	LD50 > 25 - 200 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
130-15-4	1,4-naphthoquinone				
	oral	LD50 124 mg/kg	Rat		
	inhalation vapour	ATE 0,5 mg/l			
	inhalation (4 h) dust/mist	LC50 0,046 mg/l	Rat		

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 11 of 16

Sensitising effects

May cause an allergic skin reaction. (Tetramethylene dimethacrylate; Methacrylic acid, monoester with propane-1,2-diol; Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]; 1,4-naphthoquinone)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 12 of 16

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
2082-81-7	Tetramethylene dimethacrylate					
	Acute algae toxicity	ErC50 mg/l	9,79	72 h	Desmodesmus subspicatus	
	Crustacea toxicity	NOEC mg/l	5,09	21 d	Daphnia magna (Big water flea)	
25013-15-4	Vinyltoluene					
	Acute fish toxicity	LC50 mg/l	1 - 10	96 h		
	Acute algae toxicity	ErC50 mg/l	0,319	72 h		
	Acute crustacea toxicity	EC50	9,3 mg/l	48 h	Daphnia magna (Big water flea)	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol					
	Acute algae toxicity	ErC50 mg/l	> 97,2	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	> 143	48 h	Daphnia magna (Big water flea)	
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]					
	Acute fish toxicity	LC50 mg/l	> 100	96 h		
	Acute algae toxicity	ErC50 mg/l	> 100	72 h		
	Acute crustacea toxicity	EC50	48 mg/l	48 h		
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate					
	Algae toxicity	NOEC mg/l	2,25	3 d		
38668-48-3	1,1'-(p-Tolylimino)dipropen-2-ol					
	Acute fish toxicity	LC50	17 mg/l	96 h	Danio rerio (zebrafish)	
	Acute algae toxicity	ErC50	245 mg/l	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	28,8	48 h	Daphnia magna (Big water flea)	
	Algae toxicity	NOEC mg/l	57,8	72 d	Desmodesmus subspicatus	OECD 201
130-15-4	1,4-naphthoquinone					
	Acute fish toxicity	LC50 mg/l	0,045	96 h	Oryzias latipes (Ricefish)	
	Acute algae toxicity	ErC50 mg/l	0,42	72 h		
	Acute crustacea toxicity	EC50 mg/l	0,026	48 h		
	Algae toxicity	NOEC mg/l	0,07	3 d		

12.2. Persistence and degradability

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 13 of 16

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
2082-81-7	Tetramethylene dimethacrylate			
	OECD 310	84 %	28	
25013-15-4	Vinyltoluene			
	OECD 310	36,7 %	28	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
	OECD 301C	81%	28	
130-15-4	1,4-naphthoquinone			
		39 %	5	

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2082-81-7	Tetramethylene dimethacrylate	3,1
25013-15-4	Vinyltoluene	3,35
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	0,97
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	2,17
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	4,91
38668-48-3	1,1'-(p-Tolylimino)dipropyl-2-ol	2,1
130-15-4	1,4-naphthoquinone	1,77

BCF

CAS No	Chemical name	BCF	Species	Source
25013-15-4	Vinyltoluene	100 - 320		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 14 of 16

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 15 of 16

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 75

Information according to Directive
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

Additional information

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile
work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation
(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement
concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level

DNEL: Derived No Effect Level

EC50: Effective concentration, 50%

ErC50: EC50 in terms of reduction of growth rate

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Organisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic

vPvB: very persistent and very bioaccumulative

PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations
Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Acute 1: Acute aquatic hazard, Category 1

Aquatic Chronic 1: Long-term aquatic hazard, Category 1

Aquatic Chronic 3: Long-term aquatic hazard, Category 3

Key literature references and sources for dataWebsite European Chemicals Agency: <https://echa.europa.eu>

Data sources: Supplier

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. A

Revision: 01.10.2025

Page 16 of 16

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. B

Revision: 10.02.2025

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

PASF - Polyester approved styrene free, Comp. B

UFI: TPJ5-00TG-700U-336U

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: Chemofast Anchoring GmbH
Street: Hanns-Martin-Schleyer-Str. 23
Place: D-47877 Willich
Telephone: +49 2154 8123 0
Internet: www.chemofast.de
Responsible Department: sdb@chemofast.de

Telefax: +49 2154 8123 333

1.4. Emergency telephone number:

+49 (0)551-19240 (GIZ-Nord, German and English 24/7) Note: The product is not being placed on the market in Ireland. The SDS is used for internal purposes only.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Eye Irrit. 2; H319
Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Dibenzoyl peroxide

Signal word: Warning**Pictograms:****Hazard statements**

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing vapours.
P280 Wear protective gloves and eye protection/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container to an approved waste disposal plant in accordance with local/national regulation.

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. B

Revision: 10.02.2025

Page 2 of 11

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
94-36-0	Dibenzoyl peroxide			5 - < 15 %
	202-327-6	617-008-00-0	01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H241 H319 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
94-36-0	202-327-6	Dibenzoyl peroxide	5 - < 15 %
		oral: LD50 = > 5000 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10	

Further Information

The product has been tested for aquatic toxicity. The tests show no need for classification of the product as toxic and harmful to aquatic life. Test reports are available.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. B

Revision: 10.02.2025

Page 3 of 11

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam
Extinguishing powder
Water spray jet
Carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic
Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For cleaning up**

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand
Treat the recovered material as prescribed in the section on waste disposal.
Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only outdoors or in a well-ventilated area.
Wear personal protection equipment (refer to section 8).
Avoid contact with skin, eyes and clothes.
When using do not eat, drink or smoke.

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. B

Revision: 10.02.2025

Page 4 of 11

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature: 5 - 25°C

7.3. Specific end use(s)

compound mortar B-component (hardener)

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
56-81-5	(OLD) Glycerol, mist	-	10		TWA (8 h)	
94-36-0	Benzoyl peroxid (Dibenzoyl peroxide)	-	5		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
94-36-0	Dibenzoyl peroxide			
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	13,3 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	39 mg/m ³

PNEC values

CAS No	Substance	Value
	Environmental compartment	
94-36-0	Dibenzoyl peroxide	
Freshwater		0,00002 mg/l
Marine water		0,000002 mg/l
Freshwater sediment		0,013 mg/kg
Marine sediment		0,001 mg/kg

Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the paste-like component and is therefore

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. B

Revision: 10.02.2025

Page 5 of 11

not freely available during use. The risk of dust inhalation is excluded. Exposure limits for respirable dusts are not relevant for this product.

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear eye protection/face protection. Wear safety glasses. DIN EN 166

Hand protection

Disposable gloves
Recommended material: NBR (Nitrile rubber)
Breakthrough time: > 480 min
Thickness of the glove material: > 0,2 mm
DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles)

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	solid (pasty)	
Colour:	black	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		Combustible
Lower explosion limits:		not applicable
Upper explosion limits:		not applicable
Flash point:		not applicable
Auto-ignition temperature:		not applicable
Decomposition temperature:		Start of decomposition: >35 °C
pH-Value:		The study does not need to be conducted because the substance is known to be insoluble in water.
Viscosity / kinematic:		not applicable

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. B

Revision: 10.02.2025

Page 6 of 11

Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	not applicable
Vapour pressure:	No data available
Density (at 20 °C):	1,59 g/cm ³
Relative vapour density:	not applicable
Particle characteristics:	No data available

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

The product is not: Explosive.

Self-ignition temperature

Solid:

not applicable

Oxidizing properties

Not oxidising.

Available oxygen content: 0,74 %

Other safety characteristics

Evaporation rate:

No data available

Solid content:

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

Benzoic acid

Benzene

Biphenyl

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. B

Revision: 10.02.2025

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
94-36-0	Dibenzoyl peroxide				
	oral	LD50 > 5000 mg/kg	Rat		

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Dibenzoyl peroxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information**12.1. Toxicity**

The product is not: Ecotoxic.

OECD 201 (Desmodesmus subspicatus)

IC10: (0 - 72 h) = 30 mg/l

IC50: (0 - 72 h) = 150 mg/l

OECD 202 (Daphnia magna)

EC0/NOEC (48h) = 100 mg/l

EC50 (48h) = >500 mg/l

EC100 (48h) = >>500 mg/l

OECD 203 (Danio rerio)

LC0/NOEC (96 h) : 250 mg/l

LC50 (96 h) : > 500 mg/l

LC100 (96 h) : >> 500 mg/l

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. B

Revision: 10.02.2025

Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
94-36-0	Dibenzoyl peroxide					
	Acute fish toxicity	LC50 mg/l	0,0602	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203
	Acute algae toxicity	ErC50 mg/l	0,0711	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50	0,11 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202
	Algae toxicity	NOEC mg/l	0,02	3 d	Pseudokirchneriella subcapitata	OECD 201
	Crustacea toxicity	NOEC mg/l	0,001	21 d	Daphnia magna (Big water flea)	OECD 211
	Acute bacteria toxicity	EC50)	35 mg/l (	0,5 h		OECD 209

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
94-36-0	Dibenzoyl peroxide			
	OECD 301D	71%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
94-36-0	Dibenzoyl peroxide	3,2

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. B

Revision: 10.02.2025

Page 9 of 11

allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. B

Revision: 10.02.2025

Page 10 of 11

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to Directive
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

Additional information

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile
work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**ADN: Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation
(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement
concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level

DNEL: Derived No Effect Level

EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Organisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic

vPvB: very persistent and very bioaccumulative

PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations
Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Acute 1: Acute aquatic hazard, Category 1

Aquatic Chronic 1: Long-term aquatic hazard, Category 1

Key literature references and sources for dataWebsite European Chemicals Agency: <https://echa.europa.eu>

Data sources: Supplier

according to Regulation (EC) No 1907/2006 - COMMISSION
REGULATION (EU) 2020/878

PASF - Polyester approved styrene free, Comp. B

Revision: 10.02.2025

Page 11 of 11

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)